







|                                                                                     |                                                                                                                                                                               |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <p>B-wire Connector<br/>Hot-shrinkable PVC Sleeve<br/>Wire Range:<br/>22 –26AWG insulated<br/>or 17AWG bare &amp; under<br/>2-4 wires acceptable<br/>Gel-filled available</p> |
|    | <p>B-wire Connector<br/>Molded Sleeve<br/>Wire Range:<br/>22 –26AWG insulated<br/>or 17AWG bare &amp; under<br/>2-4 wires acceptable<br/>Gel-filled available</p>             |
|   | <p>BIG B-wire Connector<br/>Molded Sleeve<br/>Large AWG range<br/>Heavy Duty<br/>Gel-filled available</p>                                                                     |
|  | <p>UY<br/>Single blade for 2-wire connection<br/>Wire range:<br/>22-26AWG</p>                                                                                                 |
|  | <p>UY2<br/>Double blades for 2-wire connection<br/>Wire range:<br/>19-26AWG</p>                                                                                               |
|  | <p>UR<br/>Double blades for 2 or 3-wires connection<br/>Wire range:<br/>19-26AWG</p>                                                                                          |

All connectors above do not require wire-stripping, and offer high reliability and efficiency of connection.

*Our job is to make your job easier!*